Soil Conditioner Mini

An attachment that pays for itself in a very short amount of time... replacing your hand labor work crew. This versatile unit rakes stones and debris to either side or straight ahead for easy pickup. Aggressive teeth on the large diameter rotor pulverize soil like an ordinary tiller, with the benefit of faster ground speed. The counter-rotating rotor moves soil ahead of it as it tills, filling in low spots and chewing off high spots. It creates perfect seedbeds and windrows. The Mini Soil Conditioner separates rocks, tears up sod, and pulverizes dirt clods. We rake and till as deep as 2".





Adjustable/removable side plates contain spillage.

Operate the attachment

in reverse or forward

motion.

FEATURES

- · Direct-drive design
- Float mount design for a more efficient operation
- · Depth changes on-the-go
- Tungsten carbide teeth
- Solid rubber wheels; with one pin can be raised out of the way for serious digging
- · Side plates are adjustable and removable
- · Spiraled teeth for windrowing
- Power angling (optional)



"A Legacy of Excellence Since 1948" www.erskineattachments.com



SPECIFICATIONS / OPTIONS

Model	Soil Conditioner Mini
Part Number	900529
Angling	Manual
Working Width	48"
Working Depth	0 - 2.5"
Maximum Angle (both ways)	25°
Overall Width	56.75"
Overall Length	55.5"
Rated Flow	9-15 GPM
Weight	470 lb.
Mounting Kit Configurations	ASV/Terex (RC/PT30)
	Bobcat (MT-52/55, 463/S70
	Toro Dingo / Vermeer / Boxer / Ditch Witch / Ramrod / Kanga
	Universal Mounting Plate for skid steers with up to 1,000 lb. rated operating capacity and within rated flow
Options	
Hydraulic Power Angling	

,			9	9
	-			
Toggle	Co	ntrol H	arnes	*ء
roggio	00	100111	unico	0

Loader Specific Wire Harness* Factory Installed Couplers

ractory instance couplers

* Applies to Hydraulic Model Only

Floating mounting system

follows the contour of the ground

Large solid urethane rubber tires allow easier maneuverability over rough terrain

Direct-drive motor gives higher production with lower maintenance



Optional: Wire harness for hydraulic models with attachment controls.



ERSKI

Optional:

Toggle Control Harness is required if skid steer is **NOT** equipped with attachment control system. Only needed when ordering hydraulic angling model.

FIT-N Char-Lynn

